



Large Slimline Smoking Shelter

Product Datasheet | Slimline Range | 24 October 2026

The Urbanfab Large Slimline Smoking Shelter provides a practical, weather-sheltered space for approximately 6–8 people. Its slimline design makes efficient use of outdoor space, with alternative applications such as sheltered staff break areas, taxi-rank waiting areas and small booths.



Large Slimline Smoking Shelter – clear UV2 PETG half-height rear and side panels included

Hot-Dip Galvanised After Fabrication

The mild steel used in Urbanfab products is hot-dip galvanised after fabrication to ISO 1461:2022. Immersion in molten zinc helps protect the external frame and accessible internal surfaces of hollow steel sections.

The bonded zinc coating provides long-term corrosion protection, helping reduce future maintenance and repairs. Learn more at urbanfab.com/why-we-galvanise/.

Dimensions and Construction

Specification	Details
Capacity	Approximately 6–8 people
Overall size	3050 mm W × 1016 mm D × 2100 mm H
Frame	50 × 25 mm RHS mild steel; hot-dip galvanised to ISO 1461:2022
Standard panels	3 mm clear UV2 PETG half-height rear and side panels
Mounting	Bolt-down base plates; concrete Anka bolts included
Assembly	Flat-packed with frame and panel assembly fixings included

Standard Configuration and Price

The Large Slimline is supplied in one standard configuration, complete with half-height rear and side panels made from 3 mm clear PETG, UV-stabilised on both sides (UV2). The panels help protect occupants from wind and rain while allowing natural light through and maintaining visibility.



Tel: 0191 534 3211 E-mail: sales@urbanfab.com Web: www.urbanfab.com

The price below is for the complete shelter, with all standard panels included.

Shelter configuration & optional extras	Ex VAT	Inc VAT
Large Slimline – half-height UV2 PETG rear and side panels included	£624.00	£748.80
Optional powder-coated frame	Please call to enquire	

Smoking Shelter Compliance

For smoking use, a roofed shelter must not be substantially enclosed under UK smoke-free regulations. At least 50% of the total surrounding wall area must remain permanently open. Nearby walls and structures must also be considered when positioning the shelter.

Optional Powder Coating

The mild-steel frame is hot-dip galvanised after fabrication to ISO 1461:2022 as standard. An optional RAL colour powder-coated finish can be applied over the galvanising to form a duplex coating system. Please see our [Powder Coating page](#) for finish options, coastal recommendations and additional benefits.

Delivery and Installation

Free UK mainland delivery is included, with standard stock configurations normally delivered within 4–5 days. For other destinations, please contact us for a quotation. Optional powder coating typically adds 3–4 working days.

The shelter is supplied flat-packed with the required frame and panel assembly fixings. Concrete ground Anka bolts are included as standard for installation on a suitable concrete surface. For alternative installation surfaces, suitable ground anchors are available at a small additional cost; we will contact you after ordering to discuss the options.

Ordering Information

Before ordering, please check the available space, installation surface, site access and nearby walls. When ordering, please let us know your bespoke requirements (where applicable), and provide your delivery postcode, preferred delivery date and any special delivery instructions, such as restricted site access, designated delivery contacts or advance notice requirements.

Prices checked against the Urbanfab product listing on 17 October 2026. A quotation confirms the final specification, price and delivery date.

Useful Links & Further Information

Large Slimline Smoking Shelter: urbanfab.com/product/large-slimline-smoking-shelter/

Smoking Shelter Range: urbanfab.com/product-category/smoking-shelters/

Why Hot-Dip Galvanising: urbanfab.com/why-we-galvanise/

Powder Coating: urbanfab.com/powder-coatings/

Delivery & Installation: urbanfab.com/delivery/

Contact Us: urbanfab.com/contact/